



\*This Part requires two clamps, part number 128-300.  
See additional drawing for information on these clamps.

**NOTES:**  
-SOME HIDDEN LINES NOT SHOWN  
-BREAK ALL SHARP CORNERS  
-REPORT ALL CHANGES TO ENGINEERING

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERNCO, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF FERNCO, INC. IS PROHIBITED.

Part Weight	2.47 lbs.
Min/Max Temp.	-30/140 Degrees F
Pressure Tested	4.3 PSI
Material	Flexible PVC
Installation Torque	60" Lbs.
Conforms to ASTM	D5926, C1173
Box Quantity	10
Clamps used	300 Series

**TOLERANCES:**  
.X= Fractional ±  
.XX= ±.02  
.XXX= ±.030  
ANG.= ±0.5°  
UNLESS OTHERWISE SPECIFIED

**DESCRIPTION:**  
Coupling 6" Ductile Iron, A/C  
Fibre x 6" Ductile Iron, A/C Fibre

1055-66

UNITS: INCHES	SIZE <b>A</b>	DESIGNER: D. Brady	SCALE not to scale
3RD ANGLE PROJECTION DO NOT SCALE DRAWING		CHECKER:	DATE: 2/1/2007
			SHEET 1 OF 1